






Catalog #: Type:
 Project: Date:
 Prepared By:
 Comments:



Cable Mount

Surface Mount

Size	A	B
11"	12" [305 mm]	4.91" [125 mm]
14"	15" [381 mm]	4.91" [125 mm]
19"	19" [483 mm]	5.66" [144 mm]

Product Weight: 2.3-6.2 lbs. by size, mounting.

FEATURES

The Single Tier Round drum is a monolithic geometric form fabricated of a perimeter skirt and lower diffused surface to provide soft, glare-free illumination. The CCFS provides a simple, clean aesthetic to applications including hotels, restaurants and residential facilities. Available in a variety of configurations and finish options.

MECHANICAL

- Standard 20-gauge light engine housing compatible with all available shades.

OPTICAL

- Available in 11", 14" & 19" diameters.¹
- 100% acrylic non-yellowing diffusers with DR additive.
- Sonically and chemically welded joints will not yellow.
- Perimeter skirt available in white satin acrylic or with 100% polyester fabric fused to acrylic sheet.
- Diffused acrylic lower panel.
- Washable with mild soap and water.
- Custom shapes, designs & finishes also available.
- 3000K, 90CRI²

WARRANTY

- 5-year limited warranty.

ELECTRICAL

- Integral electronic driver, 120V, 60 Hz.²
- Dimmable to 10% via standard Triac dimmer.

MOUNTING

- Available in surface & cable configurations.
- Cable configuration suspends from three adjustable cables & clear conductor. 96" max. suspension length.
- Shades mechanically attach to housing with three tool-less fasteners.
- Mounts to standard 4" recessed j-box (by others).

CERTIFICATIONS

- UL damp listed to US and Canadian safety standards.
- Meets Energy Star requirements.
- Compliant with JA8-2019 requirements of California Title 24.
- RoHS compliant.

(1) Nominal diameter. See line drawings for actual dimensions.

(2) Contact Sales at Sales@rlrindinc.com for non-cataloged & custom configurations.

TECHNICAL

L70 Life:	>54,000 hours
Color Consistency:	5-Step SDCM
Max. Ambient Temperature:	45° C
Min. Starting Temperature:	-20° C
Sound Rating:	Class A
Power Factor:	>0.90
THD:	<20%

LIGHT ENGINE DATA

	Light Engine Lumens ³	Input Power	Light Engine Efficacy	120V Current
17W	1,530 lm	16.9 W	90.6 LPW	0.14 A
25W	2,273 lm	24.8 W	91.5 LPW	0.22 A
32W	2,977 lm	32.0 W	93.0 LPW	0.28 A

(3) Luminaire lumens are lower due to optical losses from shade.

ORDERING INFORMATION

Example: 32W-3090-SMBN-C19-CCFS-557


32W	3090	SM	BN	C19	CCFS	557	
-----	------	----	----	-----	------	-----	--

WATTAGE	LED COLOR ¹	MOUNTING	CANOPY COVER FINISH	DIAMETER ³	SHADE STYLE	SHADE FINISH	SHADE OPTIONS
17W 25W 32W	3000K, 90CRI	SM = Surface Mount PM = Cable Mount	Blank = Surface Mount WH = White ² BN = Brushed Nickel Finish ²	C11 = 11" (17W only) C14 = 14" (25W only) C19 = 19" (32W only)	CCFS = Single Tier Drum	(See photos below) 217 = White Satin 555 = Jute 655 = Double Laminated Jute ⁴ 556 = Chocolate Linen 557 = Rapids 558 = White Linen 658 = Double Laminated White Linen ⁴ 010 = Opaque Metallic Nickel 104 = Opaque Metallic Bronze 570 = Gray Slate 580 = Black Linen	(See photos below) Blank = No Option BNT = Brushed Nickel Trim BZT = Bronze Trim 012 = Black X-Trim 118 = White X-Trim 010 = Metallic Nickel X-Trim 104 = Metallic Bronze X-Trim ROT = Red Oak X-Trim COT = Clear Lacquered Oak X-Trim


- (1) Contact Sales at Sales@rlrindinc.com for non-cataloged & custom configurations.
- (2) Indicate WH or BN finish for Cable Mount (PM) models only.
- (3) Nominal diameter. See line drawings for actual dimensions.
- (4) Double laminated finish provides 2nd outer layer of clear acrylic with light texture for improved wipe-down and reduced dirt accumulation.

Additional stained oak finishes available, contact Sales@rlrindinc.com

SHADE FINISHES



SHADE OPTIONS



COMPATIBLE DIMMER LIST

The following dimmers have been tested and verified as compatible. Additional dimmers may be compatible but have not been tested.

Lutron MACL-153M	Leviton IPL06-10Z
Lutron TGCL-153P	Leviton 6674-P0W
Lutron CTCL-153P	Leviton 6672-1LW
Lutron PD-6WCL	Leviton DLS06-1LZ

RLR Industries, Inc.
575 Discovery Place
Mableton, GA 30126

www.rlrindinc.com
Sales Inquiries: Sales@rlrindinc.com
770-948-6069