

Size	A	B
11"	12" [305 mm]	4.91" [125 mm]
14"	15" [381 mm]	4.91" [125 mm]
19"	19" [483 mm]	4.91" [125 mm]

Product Weight: 2.5-6.7 lbs. by size, mounting.

FEATURES

The Radius-Corner Square drum is a rectilinear geometric form fabricated of a square perimeter skirt with radiused corners and lower diffused surface to provide soft, glare-free illumination. The CCSQ provides a simple, clean aesthetic to a wide variety of applications. Available in a variety of configurations and finish options.

MECHANICAL

- Standard 20-gauge light engine housing compatible with all available shades.

OPTICAL

- Available in 11", 14" & 19" diameters.¹
- 100% acrylic non-yellowing diffusers with DR additive.
- Sonically and chemically welded joints will not yellow.
- Perimeter skirt available in white satin acrylic or with 100% polyester fabric fused to acrylic sheet, available in a variety of patterns.
- Diffused acrylic lower panels.
- Washable with mild soap and water.
- Custom shapes, designs & finishes also available.
- 3000K, 90CRI²

WARRANTY

- 5-year limited warranty.

ELECTRICAL

- Integral electronic driver, 120V, 60 Hz.²
- Dimmable to 10% via standard Triac dimmer.

MOUNTING

- Available in surface & cable configurations.
- Cable configuration suspends from three adjustable cables & clear conductor. 96" max. suspension length.
- Shades mechanically attach to housing with three tool-less fasteners.
- Mounts to standard 4" recessed j-box (by others).

CERTIFICATIONS

- UL damp listed to US and Canadian safety standards.
- Meets Energy Star requirements.
- Compliant with JA8-2019 requirements of California Title 24.
- RoHS compliant.

(1) Nominal diameter. See line drawings for actual dimensions.

(2) Contact Sales at Sales@rlrindinc.com for non-cataloged & custom configurations.

TECHNICAL

L70 Life:	>54,000 hours
Color Consistency:	5-Step SDCM
Max. Ambient Temperature:	45° C
Min. Starting Temperature:	-20° C
Sound Rating:	Class A
Power Factor:	>0.90
THD:	<20%

LIGHT ENGINE DATA

	Light Engine Lumens ³	Input Power	Light Engine Efficacy	120V Current
17W	1,530 lm	16.9 W	90.6 LPW	0.14 A
25W	2,273 lm	24.8 W	91.5 LPW	0.22 A
32W	2,977 lm	32.0 W	93.0 LPW	0.28 A

(3) Luminaire lumens are lower due to optical losses from shade.

RLR Industries, Inc.
575 Discovery Place
Mableton, GA 30126

www.rlrindinc.com
Sales Inquiries: Sales@rlrindinc.com
770-948-6069

ORDERING INFORMATION


Example: 17W-3090-SMBN-C11-CCSQ-558

17W	-	3090	-	SM	BN	-	C11	-	CCSQ	-	558	-	
-----	---	------	---	----	----	---	-----	---	------	---	-----	---	--


WATTAGE	LED COLOR ¹	MOUNTING	CANOPY COVER FINISH	SIZE ³	SHADE STYLE	SHADE FINISH	SHADE OPTIONS
17W	3000K, 90CRI	SM = Surface Mount	Blank = Surface Mount	C11 = 11" (17W only)	CCSQ = Radius Corner Square	(See photos below)	(See photos below)
25W		PM = Cable Mount	WH = White ²	C14 = 14" (25W only)		217 = White Satin	Blank = No Option
32W			BN = Brushed Nickel Finish ²	C19 = 19" (32W only)		555 = Jute Laminated Jute ⁴	BNT = Brushed Nickel Trim
						556 = Chocolate Linen	BZT = Bronze Trim
						557 = Rapids	
						558 = White Linen	
						658 = Double Laminated White Linen ⁴	
						010 = Opaque Metallic Nickel	
						104 = Opaque Metallic Bronze	
						570 = Gray Slate	
						580 = Black Linen	

- (1) Contact Sales at Sales@rlrindinc.com for non-cataloged & custom configurations.
- (2) Indicate WH or BN finish for Cable Mount (PM) models only.
- (3) Nominal diameter. See line drawings for actual dimensions.
- (4) Double laminated finish provides 2nd outer layer of clear acrylic with light texture for improved wipe-down and reduced dirt accumulation.

SHADE FINISHES



SHADE OPTIONS



COMPATIBLE DIMMER LIST

The following dimmers have been tested and verified as compatible. Additional dimmers may be compatible but have not been tested.

Lutron MACL-153M	Leviton IPL06-10Z
Lutron TGCL-153P	Leviton 6674-POW
Lutron CTCL-153P	Leviton 6672-1LW
Lutron PD-6WCL	Leviton DLS06-1LZ

<p>RLR Industries, Inc. 575 Discovery Place Mableton, GA 30126</p>	<p>www.rlrindinc.com Sales Inquiries: Sales@rlrindinc.com 770-948-6069</p>
---	--