






Catalog #: Type:
 Project: Date:
 Prepared By:
 Comments:



Front View



Side View



Top View

Product Weight: 1.6 lbs.

FEATURES

The Vertical Sweep wall sconce provides an understated contemporary aesthetic and soft uniform illumination to interiors including hotels, restaurants, residential and other leisure applications. Available in a variety of configurations and finish options to add a signature appearance.

MECHANICAL

- Standard 20-gauge light engine housing compatible with all available shades.

OPTICAL

- 100% acrylic non-yellowing diffusers with DR additive.
- Sonically and chemically welded joints will not yellow.
- Lens front face surface available in white satin finish or with 100% polyester fabric fused to acrylic sheet, available in a variety of patterns.
- Lens side panels are frosted white acrylic in satin finish.
- Washable with mild soap and water.
- Custom shapes, designs & finishes also available.
- 3000K, 90CRI¹

WARRANTY

- 5-year limited warranty.

ELECTRICAL

- Integral electronic driver.
- 120V, 60 Hz.¹
- Dimmable to 10% via standard Triac dimmer.

MOUNTING

- Faces mechanically attach to housing with tool-less fasteners.
- Mounts to standard 4" recessed j-box (by others).

CERTIFICATIONS

- UL damp listed to US and Canadian safety standards.
- Meets Energy Star requirements.
- Compliant with JA8-2019 requirements of California Title 24.
- Americans with Disabilities Act (ADA) compliant.
- RoHS compliant.

(1) Contact Sales at Sales@rlrindinc.com for non-cataloged & custom configurations.

TECHNICAL

L70 Life:	>54,000 hours
Color Consistency:	5-Step SDCM
Max. Ambient Temperature:	45° C
Min. Starting Temperature:	-20° C
Sound Rating:	Class A
Power Factor:	>0.90
THD:	<20%

LIGHT ENGINE DATA

	Light Engine Lumens ²	Input Power	Light Engine Efficacy	120V Current
17W	1,530 lm	16.9 W	90.6 LPW	0.14 A

(2) Luminaire lumens are lower due to optical losses from shade.

RLR Industries, Inc.
575 Discovery Place
Mableton, GA 30126

www.rlrindinc.com
Sales Inquiries: Sales@rlrindinc.com
770-948-6069

ORDERING INFORMATION

Example: 17W-3090-WM-VS-558

17W	-	3090	-	WM	-	VS	-	558
-----	---	------	---	----	---	----	---	-----

WATTAGE
17W**LED COLOR¹**
3000K, 90CRI**MOUNTING**
WM = Wall
Mount**FACE STYLE**
VS = Vertical
Sweep**FACE FINISH**

(See photos below)

217 = White Satin

555 = Jute

655 = Double Laminated
Jute²

556 = Chocolate Linen

557 = Rapids


558 = White Linen

658 = Double Laminated
White Linen²

570 = Gray Slate

580 = Black Linen

(1) Contact Sales at Sales@rlrindinc.com for non-cataloged & custom configurations.

(2) Double laminated finish provides 2nd outer layer of clear acrylic with light texture for improved wipe-down and reduced dirt accumulation.**FACE FINISHES****COMPATIBLE DIMMER LIST**

The following dimmers have been tested and verified as compatible. Additional dimmers may be compatible but have not been tested.

Lutron MACL-153M	Leviton IPL06-10Z
Lutron TGCL-153P	Leviton 6674-POW
Lutron CTCL-153P	Leviton 6672-1LW
Lutron PD-6WCL	Leviton DLS06-1LZ

RLR Industries, Inc.
575 Discovery Place
Mableton, GA 30126

www.rlrindinc.com
Sales Inquiries: Sales@rlrindinc.com
770-948-6069